

POWERATTACK



TELESCOPING
adjusts for leverage and
comfort of operator
(max length 84 inches)

LANDING GEAR
2 wheel aux trolley for easy
transport when not under
the load

**BATTERY
INDICATOR**
ON/OFF SWITCH

TWO SPEEDS
(16ft/min and 65ft/min)

**NO MEMORY
EFFECT
OR DISCHARGE**
when not in use

**24V LI-ION
BATTERY***
drives a powerful
24V 3-phase motor
with variable speed
for smooth operation
*KPA-30 only

**EMERGENCY
STOP BUTTON**

**VARIABLE
SPEED CONTROL**

AVAILABLE BATTERY OR CORDED!

EACH POWERATTACK
comes with an adjustable load
toe, an L Adaptor and an adaptor
to connect to a front skate.
The battery version also includes
2 batteries and a charge unit.



25 TON



30 TON

Accessories



ADJUSTABLE LOAD TOE
To have convenient working
height for operator



BLUETOOTH CHARGER
Connects to app VICTRON CONNECT
to monitor charge *KPA-30 only



L ADAPTOR
For when the height of the
object to push is higher



TRI-GLIDE ADAPTOR
Easily connect the Powerattack to our Tri-Glide front unit.
Rear dollies can complete a 3 point powered moving solution

Hilman Part #	KPA-25	KPA-25-230V	KPA-30
Total Capacity	*25 tons	*25 tons	*30 tons
Telescopic Length	65" (1650 mm) - 84" (2150 mm)	65" (1650 mm) - 84" (2150 mm)	65" (1650 mm) - 84" (2150 mm)
Width	15" (380 mm)	15" (380 mm)	15" (380 mm)
Weight	110 lbs (50 kg)	110 lbs (50 kg)	110 lbs (50 kg)

*Loads can be moved up to 25 to 30 tons depending on floor surface, types of skates, etc.



12 Timber Lane • Marlboro, New Jersey 07746 • USA
tel: 732.462.6277 | fax: 732.462.6355 | e-mail: sales@hilmanrollers.com

The specifications are given as general information only and are not binding. Hilman Rollers reserves the right to change specifications or make alterations to products, parts or accessory equipment at any time without prior notice and for any reason whatsoever.